

ACCESSORIES

Nozzle Extension – straight

With the straight nozzle extension, you can coat even where the spray device itself cannot reach – in narrow, deep or hard-to-reach areas.

In continuous operation, it reduces downtimes because wear parts need to be changed less often. It is mounted directly on the spray device via an adapter instead of the spray head – quickly retrofitted and the ideal addition to your existing equipment.



Available lengths
300 – 1000 mm

Available adapters for
OC1 - Schub5
LDU2 - LDU3

For wire Ø
1.6, 2.0 and 2.5 mm

Your benefits at a glance

- ✓ Greater reach: coat even narrow and concealed areas that cannot be reached with the hand-held spray device
- ✓ Ideal for automation: hard-to-reach maintenance areas are much easier to handle in automated processes
- ✓ Precisely adjustable: the adjustable nozzle system allows fine adjustment of the spray jet
- ✓ Flexible spray pattern: available with either round-jet or flat-jet nozzle system
- ✓ Fits your system: can be connected to various spray devices via suitable adapters

General Data	
Spray wire quality	DIN EN ISO 14919
Spray wire diameter	1.6 mm / 2.0 mm / 2.5 mm
Lengths (standard)	300 mm / 500 mm / 700 mm / 1000 mm (other lengths on request)
Max. spray current	600 A
Weight	0.75 kg (300 mm version)
Dimensions (example: 300 mm)	
	