

PRODUCT DATA SHEET

OSUCAS Arc Spray System

OC600Corr

with WF4 Wire Feed Gear, WFC Intermediate Trolley
and OC1 Hand-held Spray Device



The illustration of the system may differ depending on the version.

POWER SOURCE

OC600Corr

including mounted WF4 wire feed gear

The OC600Corr power source with its transformer-rectifier system has characteristic curves specially designed for arc spraying. The generously dimensioned power components ensure continuous spraying operation at 100 % duty cycle. Convection provides sufficient cooling of the power source while reducing contamination by metal dust to a minimum.

The OC600Corr is equipped with a PLC control system that monitors and controls all spray parameters. Operating faults are indicated by signal lamp codes on the power source panel and displayed in detail on the PLC display. The power source is equipped with safety devices that automatically switch the system to a safe operating state in the event of overload, overheating or pressure drop.

The compact design of the OC600Corr, combined with the large swivel and fixed castors, ensures easy manoeuvring of the power source even in harsh site conditions. Thanks to their large contact surface, the OSUCAS DC power connections provide low-loss energy transfer with minimal heat generation at the connections.



Spray current

600 A

100 % duty cycle

Spray rate

60 kg/h

Zinc


Spray rate

18 kg/h

Aluminium

The power source with a maximum spray current of 600 A (at 100 % duty cycle) stands out for:

- ✓ its compact and robust design
- ✓ easy handling with clearly legible display elements
- ✓ the clear arrangement of the controls on the inclined control panel
- ✓ large swivel and fixed castors for easy manoeuvrability, even in harsh site conditions
- ✓ optimised power connections for high energy efficiency
- ✓ the WF4 wire feed gear with its proven rubber roller system for continuous, trouble-free wire feed

Electrical Data		
Mains voltage	3 x 400 V AC	=> Other mains voltages available on request
Mains voltage tolerance	± 5 %	
Mains frequency	50/60 Hz	
Input current	< 34.6 A	
Mains fuse	63 A	
Connected load	< 24 kVA	
Max. spray current (at 100 % duty cycle)	600 A DC	
Open-circuit voltage	26 – 39 V DC	
Spray voltage	22 – 34 V DC	
Spray Wires and Spray Performance		
Spray wire quality	DIN EN ISO 14919	
Spray wire diameter	2.5 mm (other diameters on request)	
<i>Selection of approved spray wires and spray rates (at 380 A):</i>		
Zn	60.0 kg/h	
ZnAl	53.0 kg/h	
Al	18.0 kg/h	
AlMg	16.0 kg/h	
Compressed Air Supply		
Required compressed air quality	DIN ISO 8573-1 Class 1	
Compressed air temperature	Cooled down to min. 25 °C	
Nominal diameter of compressed air ring main	25 mm (1 inch)	
Nominal diameter of air hose (power source)	25 mm (1 inch)	
Connection type	Compressor coupling G1/2 inch (female thread)	
Max. inlet pressure	10 bar	
Compressed air consumption – air motor	25 m³/h	
Compressed air consumption – atomizing air	60 – 100 m³/h	
Other Data		
Weight	410 kg	
Protection class	IP 21	
Cooling type	Convection	
Test mark	CE	
Dimensions		
		

WIRE FEED


WF4 Wire Feed Gear

With its rubber roller system, the WF4 wire feed gear is used specifically for synchronous, trouble-free wire feed using the push-pull method.

The powerful asynchronous motor is completely maintenance-free and, with its fixed speed, delivers high torque. The wire feed gear supports the wire feed in the spray device, thus guaranteeing a clean and steadily burning arc.

This push-pull principle guarantees trouble-free wire feed up to a cable and hose set length of 15 m.

For greater lengths, we recommend using the OC-Speed wire feed gear with its slip clutch principle. This gear enables absolutely trouble-free wire feed even over long distances. When processing zinc wire, feeding the wire over up to 20 m is no problem. Stiff wires can also be processed with this gear.



Up to 20 m

Cable and hose set (push-pull)

WF4 –Standard

8 - 15m / various gears for different materials and Ø

OC-Speed

Wire feed up to 20 m
(without intermediate gear)

Features of the WF4 wire feed gear:

- ✓ powerful, maintenance-free asynchronous motor with high torque
- ✓ feed and pressure rollers made of special rubber material for synchronous, trouble-free wire feed up to a cable and hose set length of 15 m

Alternative: OC-Speed wire feed gear

- ✓ feed and pressure rollers made of hardened steel with integrated slip clutch for synchronous, trouble-free wire feed up to a cable and hose set length of 20 m

Electrical Data	
Motor supply voltage	3 x 400 V AC
Motor rated power	90 W
Other Data	
Weight	12 kg
Gear ratio	20:1

Depending on the configuration, power sources can be equipped with or without WF4 wire feed gear – see text in the quotation

ACCESSORIES

Wire Feed Trolley WFC380/600

The OSUCAS wire feed trolley with integrated wire feed gear and uncoiling device is an optional component – especially for corrosion protection applications – where a large working radius (cable and hose set length) is required. Compared to a standard setup with a total cable and hose set length of 10 m, integrating the wire feed trolley allows a total cable and hose set length of up to 40 m.

The power source can be positioned outside the spray area, which protects it from metal dust contamination. A further advantage is the ability to work in areas with very restricted access (e.g. manholes). For access, the OSUCAS wire feed trolley can be dismantled into its main components if required.

The illustration shows the version with the WF4 wire feed gear.

Depending on requirements, the WF6 or PF1 wire feed gear can be used as an alternative



Intermediate cable and
hose set

10 – 30 m

For spray device

**OC1 – OC-Mini
LDU3 – LDU2**

Wires

**Solid and cored
wires**


Features of the WFC380/600 wire feed trolley

- ✓ Extension of the working radius by up to 30 m
- ✓ Version available for OC380Corr and OC600Corr
- ✓ Large swivel and fixed castors for easy manoeuvrability even in harsh site conditions
- ✓ Removable attachments - specially for use in boilers, for access through a manhole (wire feed gear, uncoiling device, wheels and handles can be removed)
- ✓ Integrated connections on the trolley for tidy cable and hose routing
- ✓ Version available for OC380Corr and OC600Corr
- ✓ Optimised power connections for high energy efficiency
- ✓ Combi uncoiling device for processing all common spool types (reel, mandrel, basket)
- ✓ Can also be used with wire from drums
- ✓ Same feed system as on the standard systems – no additional spare parts stock

To use the wire feed trolley, the power source must be prepared for it – retrofitting possible? Talk to us!



Optional Components

- ✓ Extension cable and hose sets with quick-release couplings
- ✓ Remote control with signal lamps, reset and wire feed buttons




Key Data	
Max. length of extension cable and hose set (power source – trolley)	30 m
Max. spray current (at 100 % duty cycle)	380 A / 600 A
Weight	42 kg / 50 kg

Configuration example of the wire feed trolley



OC380Corr-WF4 with OC1 combined with WFC380 incl. WF4 wire feed gear and extension cable and hose set



OC400Tech with OC-Mini combined with WFC380 incl. PF1 wire feed gear and extension cable and hose set

To use the wire feed trolley, the power source must be prepared for it – retrofitting possible? Talk to us!

SPRAY DEVICE

OC1 Corr

With its closed nozzle system, the OC1-Corr spray device is ideal for processing corrosion protection wires. The special geometry of the nozzle system components enables very fine atomization of the molten particles, resulting in a correspondingly fine spray coating with low surface roughness. This offers considerable potential for saving paint in subsequent top coats.

In combination with the wire feed gear on the power source, the wire feed built into the spray device allows the use of cable and hose sets up to 20 m in length.

The OSUCAS DC power connections provide low-loss energy transfer with minimal heat generation and improved conductivity. This keeps the energy where it belongs – in the spraying process.



600 A

Max. current (100 % duty cycle)

20 m

Max. cable and hose set length
(without intermediate gear)

2.4 kg

without cable and hose set

Features of the OC1 spray device:

- ✓ housing made of fibre-reinforced material for a long service life
- ✓ compact design and low weight
- ✓ modern and easy handling (including the dead man's switch with reflective light sensor)
- ✓ optimised power connections for high energy efficiency
- ✓ can be connected to (almost) all OSU power sources
- ✓ reduced wear part requirements thanks to a feed unit driven directly by the air motor

Spray Wires and Spray Performance	
Spray wire quality	DIN EN ISO 14919
Spray wires	Zn - ZnAl - Al - AlMg5
Spray wire diameter	2.5 mm (other diameters on request)
Max. spray current (at 100 % duty cycle)	600 A
Compressed Air Supply	
Required compressed air quality	DIN ISO 8573-1 Class 1
Compressed air temperature	Cooled down to min. 25 °C
Compressed air consumption – air motor	25 m³/h
Compressed air consumption – atomizing air	60 – 100 m³/h
Other Data	
Weight	2.4 kg (without cable and hose set)

ACCESSORIES

Optional Accessories



Combi uncoiling device

for processing wire on spools

The uncoiling device is mounted directly on the power source, enabling mobile use, e.g. on construction sites.

Our new Combi uncoiling device gives you the flexibility to use wires on all available spool types (reel, mandrel and basket spools). With just a few simple steps, you can convert this uncoiling device to the spool type of your choice in no time.



Drum cover with de-coiling device

for processing endless wire from drums

The drum cover protects the wire in the drum from dust and other contamination. The de-coiling device is mounted directly on the cover.

The drum cover is made of robust, transparent material that provides an overview of the amount of wire in the drum at all times. An access opening covered with a rubber flap allows the wire to be threaded in easily.

The drum cover fits drum diameters of 505 - 574 mm (variably adjustable).




Mobile wire feed trolley

to extend the working radius by up to 40 m

The OSUCAS wire feed trolley with integrated wire feed gear was specially developed for applications that require a large working radius – as is typical in corrosion protection.

Depending on requirements, it is available either with a Combi uncoiling device for spools or for use with wire in drums.

By integrating the wire feed trolley into the respective standard setup of the system, total cable and hose set lengths of up to 40 m can be achieved – depending on the material being processed.



Angled nozzle extension

for coating hard-to-reach areas

The angled nozzle extension is a spray extension for the internal coating of pipes as well as for coatings in hard-to-reach areas. It is attached to the spray device with a suitable adapter (instead of the spray head).

Available in different lengths and with various adapters.